



TEKNISK INFORMATION



9,15 m



3,10 m



3700 kg
+ motor



390 l



135 l



0,90 m



300-370 hk
221-272 kW



4+2



C



10

TESTRAPPORTER

Volvo Penta D6 - 370 HP. DP-H G5

Load 2 persons

Delta Boats reserves the right to make changes to installed propeller without prior notice!

RPM	Speed 1. [kn]	Speed 2. [kn]	Average kn	Fuel 1. [l / h]	Fuel 2. [l / h]	Fuel average [l / h]	Fuel [l / nm]	Noise 1.dB	Noise 2.dB	Average db.
600	3,8	4,1	4,0	1,7	1,1	1,4	0,35	69	67	68
1000	6,1	6,3	6,2	3,8	4	3,9	0,63	70	70	70
1500	7,9	8,1	8,0	13	13	13,0	1,63	75	75	75
2000	11,1	11,3	11,2	30	29	29,5	2,63	79	79	79
2200	14,3	14,2	14,3	37	36	36,5	2,56	83	81	82
2400	20,4	20,4	20,4	33	32	32,5	1,59	80	81	81
2600	24,2	24,4	24,3	37	36	36,5	1,50	81	81	81
2800	27,4	27,4	27,4	41	40	40,5	1,48	83	83	83
3000	30,4	30,4	30,4	48	48	48,0	1,58	82	82	82
3200	32,8	33,1	33,0	54	53	53,5	1,62	83	83	83
3400	35,6	36,1	35,9	63	62	62,5	1,74	83	84	84
3640	38,6	38,9	38,8	78	78	78,0	2,01	84	84	84

Performance figures listed above may vary up to 8 % depending on installed accessories and weather conditions

Mercury diesel TDI 4,2 - 370 HP. Bravo 3XR

Load 2 persons

Delta Boats reserves the right to make changes to installed propeller without prior notice!

RPM	Speed 1. [kn]	Speed 2. [kn]	Average kn	Fuel 1. [l / h]	Fuel 2. [l / h]	Fuel average [l / h]	Fuel [l / nm]	Noise 1.dB	Noise 2.dB	Average db.
600	3,7	3,7	3,7	1,1	1,1	1,1	0,30	-	-	-
1000	5,5	5,5	5,5	3,4	3,4	3,4	0,62	-	-	-
1500	7,3	7,3	7,3	6,8	6,8	6,8	0,93	-	-	-
1800	8,1	8,1	8,1	13	13	13,0	1,60	-	-	-
2000	8,6	8,6	8,6	18,7	18,7	18,7	2,17	-	-	-
2200	10,4	10,4	10,4	23,2	23,2	23,2	2,23	-	-	-
2400	12,4	12,4	12,4	28	28	28,0	2,26	-	-	-
2600	15,4	15,4	15,4	31,7	31,7	31,7	2,06	-	-	-
2800	21	21	21,0	34,2	34,2	34,2	1,63	-	-	-
3000	24,5	24,5	24,5	38,8	38,8	38,8	1,58	-	-	-
3200	27,1	27,1	27,1	45,3	45,3	45,3	1,67	-	-	-
3400	29,7	29,7	29,7	52	52	52,0	1,75	-	-	-
3600	31,8	31,8	31,8	56,1	56,1	56,1	1,76	-	-	-
3800	33,6	33,6	33,6	61,8	61,8	61,8	1,84	-	-	-
4000	35,6	35,6	35,6	68,8	68,8	68,8	1,93	-	-	-
4200	37,1	37,1	37,1	75	75	75,0	2,02	-	-	-
4315	38,2	38,2	38,2	80	80	80,0	2,09	-	-	-

Performance figures listed above may vary up to 8 % depending on installed accessories and weather conditions